

MATERIAL SAFETY DATA SHEET

Approved by Quickwall Australia Pty Ltd

144 Granite St
Geebung Q 4034
Ph: 07 3216 5544
Fx: 07 3216 5533
www.quickwall.com.au
info@quickwall.com.au



Product Name: **QUICKWALL CEMENT**

Date of Issue: 19/04/2006
Infosafe No N/A

IDENTIFICATION

Product Name	QUICKWALL MINERAL BASED CEMENT
UN Number	None Allocated
DG Class	None Allocated
Packing Group	None Allocated
Hazchem Code	None Allocated
Classified	Nuisance Dust
Poisons Schedule	Not Scheduled
Product Use	Surface Coatings – used as a substrate repair, basecoat and finishing plaster in conjunction with a liquid polymer, QW 2000.
Other Names	Regular Skimcoat, Hi-Build Skimcoat, Lightweight, Skimcoat, White Hi-Build, White Regular Skim, Quicksand, Quicktrowel, Sandstone, Plaster Plus, Traditional Render, Santa Fe, Spray Tile, Quick Spray.

PHYSICAL DATA / PROPERTIES

Appearance	A white to grey finely ground, odourless powder, silica sands, and additives.
Melting Point	1200 deg. C
Combustibility	Non-combustible and non-explosive.
Unit Mass	2,400 – 2,800 kg/m ³
Flash Point	Not applicable
Solubility in Water	Slightly soluble in water - Hardens when mixed with water

INGREDIENTS / CHEMICAL ENTITY

		% by weight
Tricalcium Silicate	3CaO.SiO ₂	25 – 70
Dicalcium silicate	2CaO.SiO ₂	10 - 50
Tricalcium Aluminate	CaO.Al ₂ O ₃	1 – 14
Tetra Calcium Alumina Ferrite	4CaO.Al ₂ O ₃ .Fe ₂ O ₃	1 – 20
Gypsum		4 – 7
Minimal amounts of	CaO, MgO, Na ₂ SO ₄ , K ₂ SO ₄	
Traces of hexavalent chrome		
Various selected aggregates		

HEALTH HAZARD INFORMATION

HEALTH EFFECTS

Acute – Swallowed	Quickwall Cement is classified as a nuisance dust. Exposure can irritate skin, eyes, and mucous membrane.
Long Term Exposure	Wet Quickwall Cement can dry the skin and cause alkali burns. In dust form, it can irritate the eyes and upper respiratory system. There may be trace amounts of hexavalent chromium present in and in some individuals this may cause dermatitis.

FIRST AID

Swallowed	Wash mouth and lips with water and seek medical attention.
Eyes	Irrigate eyes immediately and repeatedly with clean water and seek medical

Skin	advice.
Inhaled	Wash with soap and water. Move to fresh air and wash with water and seek medical attention if effects persist.
First Aid Facilities	Ensure eye wash bath and safety shower are readily accessible.

PRECAUTIONS FOR USE

Exposure Limits Name	Quickwall Cement is classified as an inert nuisance dust with a TLV of 10 mg/m ³ . Wet cement on the skin can cause alkali burns. Continued exposure to individuals allergic to chromium could cause severe allergic dermatitis.
Ventilation	Local exhaust can be used if necessary to control airborne dust levels. Persons with a history of respiratory illness should avoid work places with high dust levels.
Personal Protection	In dusty environments, the use of filter masks as in AS1716 (Class L) and tight fitting goggles is advised. Use of barrier creams or impervious gloves, boots and clothing to protect the skin from contact with wet Cement is recommended. Following work with Quickwall Cement workers should shower with soap and water.
Flammability	Quickwall Cement is non-combustible.

SAFE HANDLING INFORMATION

Handling and Storage	Quickwall Cement is distributed in plastic lined paper sacks. Storage must be designed to prevent ingress of moisture which would cause the Cement to harden. Transport may be by road, rail or ship.
Spills & Disposal	If spilled, Quickwall Cement may be cleaned up using dry methods that do not disperse dust into the air. Avoid breathing the dust and wear protective clothing if necessary. Emergency procedures are not required. Cement can be treated as a common waste for disposal or returned to the container for later use if it is not contaminated or wet.

CONTACT POINT

Contact	Quickwall Australia Pty Ltd 144 Granite Street Geebung, Qld., 4034 Ph: (07) 3216 5544 Fx: (07) 3216 5533
---------	--

Quickwall make no representation as to the completeness and accuracy of the data contained in this data sheet. It is the user's obligation to evaluate and use this product safely, and to comply with all relevant Federal, State and Local Government laws and regulations. Quickwall shall not be responsible for loss, damage or injury resulting from reliance upon or failure to adhere to any recommendations or information contained herein, from abnormal use of the material, or from any hazard inherent in the nature of the material.