



2 Pack Mineral Based **SKIMCOAT** SURFACE PREPARER

DESCRIPTION

QUICKWALL **SKIMCOAT** is a highly modified flexible 2 pack polymer cement for :

1. Preparing most substrates as a base coat for selected Quickwall Applied Finishes.
2. Obliterating defective joints in Hebel Blocks, Hebel Power Panels, Masonry Blocks, Bricks, etc.
3. A bonding base coat to Polystyrene and Polyurethane sheets reinforced with alkali resistant mesh.
4. A base coat plaster for QUICKCLAD wall cladding systems or white set plaster.

GRADES

- **Regular Skimcoat**
- **High-Build Skimcoat** for filling deep joints
- **QuickClad Skimcoat** for QuickClad Systems
- **Light weight Skimcoat** for high fire risk substrates

SPECIAL FEATURES

- Will not go drummy like sand / cement render often does.
- Will not delaminate like acrylic coatings / acrylic render often does.
- Not effected by humidity like high build acrylic coatings are.
- High Impact, Flexural, Mechanical and Abrasion strengths.
- Unequalled bond to most substrates. Permanent base coat.
- Excellent protection for single skin construction.
- Excellent freeze thaw ability and exterior weathering.
- Eliminates the cost of plastering on most projects.
- Resistant to most chemicals, no shrinkage.
- Non - combustible, Ease of workability / application.
- Bond to Ceramic Tiles with increased 1:1 Quickwall Polymer ratio.

SURFACE PREPARATION

Quickwall polymer modified mineral coatings over acrylic painted surfaces are only as good as the original paint bond to the substrate. Generally painted surfaces/resin coated aggregate surfaces are water blast cleaned first, sealed with Quickwall polymer diluted 5:1 and Skimcoat polymer increased to 2:1 prior to the Quickwall applied finish. Top coat with minimum 2 coats of exterior paint.

The standard manufacturers warranty does not apply to painted surfaces. Approved applicators pricing coating to previously painted surfaces are not expected to know the condition of the original bond or the type/quality of paint originally used on walls or roofs. If in doubt – consult Quickwall Technical line or do not proceed.

APPROVED FOR

Government Projects, Defence Housing Authority, Commercial and Domestic applications.

GUARANTEE

Ten years when applied by an Approved Applicator and in accordance to Quickwall specification.

SPECIFICATION

1st Coat: Apply Quickwall **SKIMCOAT**

2nd Coat: Apply Selected **QUICK FINISH**

3rd Coat: Apply 1 coat of **AQUASEAL**

4th Coat: Apply 1 coat of **AQUASEAL**

Notes: For best results Mid range yellows and reds apply 3 coats of Aqua Seal.

Notes: For hi-rise buildings with difficult logistics apply 3 coats of Aqua Seal.

Website

www.quickwall.com
www.quickwall.com.au



2 Pack Mineral Based

SKIMCOAT

SURFACE PREPARER



1. Block wall



2. Apply High-Build SKIMCOAT



3. High-Build SKIMCOAT closeup



4. High-Build SKIMCOAT