



# 2 Pack Mineral Based **QUICKSAND**

## SMOOTH / FLAT CEMENT COATING SYSTEM

### DESCRIPTION

QUICKWALL **QUICKSAND** is a very popular grey 2 pack polymer modified cementitious plaster for Interior or Exterior wall finishing.

- Is often architecturally described as a **half way coating** - half way between a fine flat texture coating and a smooth scrub fine render finish.
- Is a project home builders interior wall coating favourite, due to its attractive fine sanded finish, durability, impact resistance and speed of application.

Applied over Quickwall Skimcoat, this quality thin film technology product is free hand applied and finished with plastic trowels to a flat-sanded finish due to its high adhesive content.

On completion, the applied finish is coated with an exterior premium grade paint.

### SUITABLE FOR

- Bricks
- Concrete
- Single Skin Masonry Blocks
- Hebel Power Panels
- Hebel Blocks
- Quick Clad
- Quick Panel
- Quick Block Building Systems,
- Polystyrene and Polyurethane treated with Quickwall Skimcoat.

### SPECIAL FEATURES

- Environmentally friendly, wash up in water.
- Applicator friendly - is a fast flat red trowel float finish, much quicker to apply and finish than solid sand cement render.

### SURFACE PREPARATION

All surfaces to be free of oil, dust, loose mortar and all other contaminants prior to any application. For masonry substrates Water to Polymer ratio is 4 : 1

### Even Substrates

Apply Quickwall **REGULAR SKIMCOAT** prior to QUICKSAND application.

### Uneven Substrates

Apply Quickwall **HIGH BUILD SKIMCOAT** prior to QUICKSAND application.

### PAINTING

The substrate can be painted after 48 hours under normal conditions.

### APPROVED FOR

Government Projects, Defence Housing Authority, Commercial and Domestic applications.

### GUARANTEE

Ten years when applied by an Approved Applicator and in accordance to Quickwall specification.

### SPECIFICATION

1<sup>st</sup> Coat: Apply Quickwall SKIMCOAT

2<sup>nd</sup> Coat: Apply Selected **QUICKSAND**

3<sup>rd</sup> Coat: Apply 1 coat of AQUASEAL

4<sup>th</sup> Coat: Apply 1 coat of AQUASEAL

Notes: For best results Mid range yellows and reds apply 3 coats of Aquaseal.

Notes: For hi-rise buildings with difficult logistics apply 3 coats of Aquaseal.

Website

[www.quickwall.com](http://www.quickwall.com)  
[www.quickwall.com.au](http://www.quickwall.com.au)