



# 2 Pack Mineral Based

# QUICKTROWEL

## VERTICAL – SCRATCH FINISH COAT

<b>DESCRIPTION</b>	<b>QUICKTROWEL</b> is a seamless premium grade flat textured, <b>vertical “scratch-coat finish”</b> . Ageless award winning coating system. Excellent for the protection and decoration of single skin buildings. <b>QUICKTROWEL</b> economically obliterates defective substrates. <b>QUICKTROWEL</b> is a permanent “ 2 pack “ polymer modified mineral system finish.
<b>GRADES</b>	1.5 mm, 2.0 mm and 3.0 mm
<b>SUITABLE FOR</b>	<ul style="list-style-type: none"> <li>• Single Skin Masonry Blocks</li> <li>• Clay Bricks</li> <li>• Concrete</li> <li>• Tilt-up Panels</li> <li>• Hebel Products</li> <li>• Quick Clad</li> <li>• Polystyrene</li> <li>• Quick Block</li> <li>• Quick Panel</li> <li>• Quickwall Building Systems</li> </ul>
<b>SPECIAL FEATURES</b>	<ul style="list-style-type: none"> <li>• Will not go drummy like sand / cement render often does.</li> <li>• Does not delaminate, peel, blister or bubble like most acrylic coatings.</li> <li>• Can be applied to dry or damp substrates.</li> <li>• Will not wash off with wind driven rainwater after five minutes of application.</li> <li>• Environment friendly and easy to use in any climate.</li> <li>• Fast application provides early completion schedules.</li> <li>• A permanent tough durable attractive and popular finish.</li> </ul>
<b>Even Substrates</b>	Apply Quickwall SKIMCOAT prior to <b>QUICKTROWEL</b> , or consult a representative.
<b>Uneven Substrates</b>	Apply Quickwall HIGH-BUILD SKIMCOAT prior to <b>QUICKTROWEL</b> .
<b>PAINTING</b>	The substrate can be painted after 48 hours under normal conditions.
<b>APPROVED FOR</b>	Government Projects, Defence Housing Authority, Commercial and Domestic applications.
<b>GUARANTEE</b>	Ten years when applied by an Approved Applicator and in accordance to Quickwall specification.

### SPECIFICATION

- 1<sup>st</sup> Coat: Apply Quickwall SKIMCOAT
- 2<sup>nd</sup> Coat: Apply Quickwall **QUICKTROWEL**
- 3<sup>rd</sup> Coat: Apply 1 Coat of AQUASEAL
- 4<sup>th</sup> Coat: Apply 1 coat of AQUASEAL
- Notes: For best results Mid range yellows and reds apply 3 coats of Aquaseal.
- Notes: For hi-rise buildings with difficult logistics apply 3 coats of Aquaseal.

Website

[www.quickwall.com](http://www.quickwall.com)  
[www.quickwall.com.au](http://www.quickwall.com.au)



**2 Pack Mineral Based**

# **QUICKTROWEL**

## **VERTICAL – SCRATCH FINISH COAT**



**Mixing texture**



**Applying 2mm**



**Polystyrene trowel**



**2mm closeup QuickTrowel**