



# 2 Pack Mineral Based **SANDSTONE** CIRCULAR – FINISH COAT

<b>DESCRIPTION</b>	<p>QUICKWALL <b>SANDSTONE</b> mimics the face of a freshly cut sandstone block. Quickwall SANDSTONE is generally applied over Quickwall SKIMCOAT to prepare the substrate.</p> <p>Quickwall SANDSTONE is a 2 pack, polymer modified, mineral based wall coating, which can be trowel or machine applied.</p> <p>Quickwall SANDSTONE economically obliterates defective substrates and is excellent for the protection and decoration of single skin masonry walls. Unlike natural sandstone, Quickwall SANDSTONE exhibits a dense final finish and optimises dirt rejection after painting.</p>
<b>GRADES</b>	1.5 mm, 2.0 mm and 3.0 mm
<b>SUITABLE FOR</b>	<ul style="list-style-type: none"> <li>• Single Skin Masonry Blocks</li> <li>• Clay Bricks</li> <li>• Concrete</li> <li>• Tilt-up Panels</li> <li>• Hebel Products</li> <li>• Quick Clad</li> <li>• Polystyrene</li> <li>• Quick Block</li> <li>• Quick Panel</li> <li>• Quickwall Building Systems</li> </ul>
<b>SPECIAL FEATURES</b>	<ul style="list-style-type: none"> <li>• Will not go drummy like sand / cement render often does.</li> <li>• Does not delaminate, peel, blister or bubble like most acrylic coatings.</li> <li>• Can be applied to dry or damp substrates.</li> <li>• Will not wash off with wind driven rainwater after five minutes of application.</li> <li>• Environment friendly and easy to use in any climate.</li> <li>• Fast application provides early completion schedules.</li> <li>• A permanent tough durable attractive and popular finish.</li> </ul>
<b>Even Substrates</b>	Apply Quickwall SKIMCOAT prior to Quickwall <b>SANDSTONE</b> , or consult a representative.
<b>Uneven Substrates</b>	Apply Quickwall HIGH-BUILD SKIMCOAT prior to Quickwall <b>SANDSTONE</b> .
<b>PAINTING</b>	The substrate can be painted after 48 hours under normal conditions.
<b>APPROVED FOR</b>	Government Projects, Defence Housing Authority, Commercial and Domestic applications.
<b>GUARANTEE</b>	Ten years when applied by an Approved Applicator and in accordance to Quickwall specification.

## SPECIFICATION

- |                       |   |
|-----------------------|---|
| 1 <sup>st</sup> Coat: | Apply Quickwall SKIMCOAT  |
| 2 <sup>nd</sup> Coat: | Apply Quickwall <b>SANDSTONE</b>  |
| 3 <sup>rd</sup> Coat: | Apply 1 Coat of AQUASEAL  |
| 4 <sup>th</sup> Coat: | Apply 1 coat of AQUASEAL  |
| Notes:                | For best results Mid range yellows and reds apply 3 coats of Aquaseal.    |
| Notes:                | For hi-rise buildings with difficult logistics apply 3 coats of Aquaseal. |

Website

[www.quickwall.com](http://www.quickwall.com)  
[www.quickwall.com.au](http://www.quickwall.com.au)



**2 Pack Mineral Based**

**SANDSTONE**

**CIRCULAR FINISH COAT**



**Red trowel technique**



**2 mm Sandstone Finish**