



Acrylic

QUICKROLL

low-medium-high TEXTURE FINISH

DESCRIPTION	QUICKROLL is a seamless roller or spray-applied wall finish with texture ranging from flat orange peel to medium and thick High-Builds. QUICKROLL provides longevity and excellent fungi, bacteria and algae protection. Excellent UV resistance and elastomeric qualities to bridge fine cracks.
GRADES	Black Roller = Low Build Blue Roller = Medium Build Yellow roller = High Build
DISPENSING	10 litre, 20 litre & 200 litre packs.
COVERAGE	1 x 20 litre pail covers (approx.) 33 m ² + depending on the porosity of the substrate. Clean up in water.
SUITABLE FOR	<ul style="list-style-type: none">• Bricks• AAC• Concrete• Cement sheet• Masonry Blocks• Fly Ash Blocks• QuickClad, and most properly prepared substrates.
Uneven Substrates	Apply Quickwall SKIMCOAT or RENDER masonry surfaces flat prior to sealing the substrate with Quickwall sealer. QUICKROLL application topcoat with quality paint (see special feature).
Even Substrates	Fill air holes with Quickwall joint repair, sand flat, seal with Quickwall sealer and apply QUICKROLL direct to the shaded substrate.
SPECIAL FEATURES	An economical, versatile user-friendly roll-on finish that may be colour tinted closely to the topcoat. By selecting the appropriate roller sleeve (shown above) the nominated build is achieved.
APPROVED FOR	Government Projects, Defence Housing Authority, Commercial and Domestic Applications.
GUARANTEE	Seven years when applied by approved applicators in accordance to the Quickwall Specification.

SPECIFICATION

1 st Coat:	Apply Quickwall PRIMER
2 nd Coat:	Apply Quickwall QUICKROLL
3 rd Coat:	Apply 1 coat Quickwall AQUASEAL
Notes:	For best results Mid range yellows and reds apply 3 coats of Aquaseal.
Notes:	For hi-rise buildings with difficult logistics apply 3 coats of Aquaseal.

Website
www.quickwall.com
www.quickwall.com.au