



# Acrylic **SANDSTONE** CIRCULAR FINISH COAT

<b>DESCRIPTION</b>	The overall appearance of QUICKWALL <b>ACRYLIC SANDSTONE</b> is similar to that of Quickwall's seamless polymer modified mineral based SANDSTONE circular scratch coating system, resembling the face of a freshly cut sandstone block.
<b>GRADES</b>	1.5 mm, 2mm and 3mm. Grain increments.
<b>SUITABLE FOR</b>	Substrates that experience <i>movement</i> such as cement sheet cladding fixed to steel stud frame walls. (Under sunny conditions the cement sheet expands in the opposite direction to steel stud frame walls, therefore the enhanced flexibility of <b>ACRYLIC SANDSTONE</b> is ideal to withstand reasonable movement.)
<b>APPLICATION</b>	<ol style="list-style-type: none"><li>1. Apply QW PRIMER.</li><li>2. Flush and set all joints with QW Jointing Compound.</li><li>3. While wet place 50mm wide alkali resistant QUICKCLAD mesh over joints. Trowel additional Jointing Compound over reinforcing mesh, feather out and allow to dry to a flat finish.</li><li>4. <u>Option to rectify undulations on substrate</u> It is preferred by Quickwall that an application of regular SKIMCOAT at 2:1 polymer be applied over substrate and joins prior to finish coat.</li><li>5. Apply <b>ACRYLIC SANDSTONE</b>.</li><li>6. Apply 2 coats of QW AQUASEAL.</li></ol>
<b>SUBSTRATES</b>	Fibre-cement sheets must be properly fixed in accordance to the manufacturer's specifications prior to <b>ACRYLIC SANDSTONE</b> application. (See <i>Spec Sheets on 'New &amp; Existing Cement Sheet' and 'Jointing Compound'</i> .)  After preparation, the substrate must be dry before applying <b>ACRYLIC SANDSTONE</b> . Rendered substrates or Quickwall Skimcoated substrates over bricks, blocks or concrete will be flat and free from undulations.
<b>SPECIAL FEATURES</b>	The product is environment and applicator friendly, exhibiting good algae, fungi and UV resistance.
<b>NOTE</b>	<b>ACRYLIC SANDSTONE</b> will be top-coated with at least 2 coats of Quickwall AQUASEAL membrane paint or good quality exterior paint to complete the system.  The unethical practice of applying any acrylic coatings without membrane top-coating is <b>Not Acceptable</b> and should be avoided.
<b>GUARANTEE</b>	Seven years when applied by approved applicators in accordance to Quickwall Specification.

## SPECIFICATION

1 <sup>st</sup> Coat:	Apply Quickwall PRIMER
2 <sup>nd</sup> Coat:	Apply Quickwall SKIMCOAT (recommended)
3 <sup>rd</sup> Coat:	Apply Quickwall <b>ACRYLIC SANDSTONE</b>
4 <sup>th</sup> Coat:	Apply Quickwall AQUASEAL
5 <sup>th</sup> Coat:	Apply Quickwall AQUASEAL

Note: The exception is where ACRYLIC SANDSTONE is tinted to the top coat of paint then generally one coat of paint is sufficient depending on the selected colour.

Website  
[www.quickwall.com](http://www.quickwall.com)  
[www.quickwall.com.au](http://www.quickwall.com.au)