



QUICKGRIP

MULTI PURPOSE ADHESIVE - FILLER

| | |
|-------------------------|---|
| DESCRIPTION | QUICKWALL QUICKGRIP is an acrylic copolymer putty adhesive. |
| SUITABLE FOR | Designed with extended binding time, QUICKGRIP bonds QUICKCLAD rigid fire retardant insulation boards to timber or metal studs. The 12 hour bond time is retarded to allow extended working times while working with the rigid sheets. This allows the installer sufficient time to position the sheets accurately prior to mechanically fixing. QUICKGRIP will be used on all horizontal and vertical joints to insure positive mechanical strengths at the joints. |
| SPECIAL FEATURES | <ul style="list-style-type: none">• Excellent resistance from microbial attacks and the adhesive remains flexible for extended long life.• No harmful solvents are used in the production of QUICKGRIP.• Applicator and environment friendly with a shelf life of approximately twelve months. |
| COVERAGE | Bulk 20 litre pails provide an economical alternative compared to small, expensive adhesive tubes. 1x 20 litre QUICKGRIP adhesive pail is generally sufficient to spot adhere approximately 200 m ² of wall area. |
| WASH UP / CARE | Wash up tools in water, however, should QUICKGRIP droppings be overlooked the surplus can be mechanically scrapped from the substrate and reduced with xylene. Wash up hands in water. |
| APPROVED FOR | Government sector projects, Defence housing Authority projects, Commercial and Private applications. |

SPECIFICATION

- 1st Step: Insure **QUICKGRIP** is spot applied to a clean and oil-free substrate.
- 2nd Step: Apply Quickwall **QUICKGRIP** in spots with a spatula.
- 3rd Step: Press rigid insulation board against stud with a slight sideways movement prior to fixing.
- 4th Step: Apply **QUICKGRIP** with a spatula to all joints prior to mechanical fixing.
- Note: Replace lid on container when not in use.

Website

www.quickwall.com
www.quickwall.com.au