



# NON-SOLVENT BASED JOINTING COMPOUND

## MULTI-USE JOINT FILLER

<b>DESCRIPTION</b>	<b>QUICKWALL JOINTING COMPOUND</b> is a tough universal water based filler compound ready to use straight from the pail for both external and internal applications to bridge joints on expanding and retracting substrates. It is a flexible co-polymer jointing compound.
<b>SUITABLE FOR</b>	<b>QUICKWALL JOINTING COMPOUND</b> will retain its elastomeric ability enabling it to be used in many applications such as: <ul style="list-style-type: none"><li>• Flush out joints in Tilt Tech pre-stressed flooring systems</li><li>• Cement sheet abutments</li><li>• Gap filler to off form concrete</li><li>• Patch repair with alkali resistant fibreglass mesh to joints.</li><li>• Expansion joint filler</li></ul>
<b>SPECIAL FEATURES</b>	<ul style="list-style-type: none"><li>• Minimum shrinkage and can be worked thinly to a feather-edge without powdering or breaking down.</li><li>• Has excellent keying ability.</li><li>• Is compatible to all Quickwall construction products and virtually all substrate building materials.</li><li>• Extremely resistant to all forms of fungicides, bacteria; and application in tropical environs have not suffered after many years of extended use.</li><li>• Environment and applicator friendly.</li></ul>
<b>NOTE</b>	Wash up in water.
<b>APPROVED FOR</b>	Government Projects, Defence Housing Authority, Commercial and Domestic applications.

### SPECIFICATION

- 1<sup>st</sup> Step: Apply Quickwall PRIMER to substrate.
- 2<sup>nd</sup> Step: Apply Quickwall **JOINTING COMPOUND** with appropriate tools.
- 3<sup>rd</sup> Step: Place alkali resistant mesh into **JOINTING COMPOUND** where required.
- 4<sup>th</sup> Step: Re-Apply one coat of **JOINTING COMPOUND** and flush outer joints to a feather edge.
- Note: Replace lid on pail when not in use.

Website

[www.quickwall.com](http://www.quickwall.com)  
[www.quickwall.com.au](http://www.quickwall.com.au)